



## EAST ALABAMA MOTOR SPEEDWAY 2019 ROAD WARRIOR TECHNICAL RULES

\*\*Rules new for 2019 will be highlighted in **BLUE**.

**Attention Racers: All cars and components must be completely stock unless otherwise stated in the rules below. If it is not mentioned or specified below it is NOT a gray area to play in. If it does not say you can do it below then you better not do it.**

### **CARS ALLOWED:**

- A. Any full bodied, and full frame sedan, example, Monte Carlo, standard or Metric Frame allowed.
- B. Camaro, Mustang, or Nova type cars allowed.

### **WEIGHT:**

- A. 3200lb with driver.
- B. 602 crate engine 3200lb with driver. (No Rebuilds)
- C. All cars must have weight posted on right side of roof.

### **ENGINE:**

- A. 350 4.060 bore Small Block maximum, No 400 engines or Big Blocks.
- B. 602 crate engine (No Rebuilds)

### **CRANKSHAFT:**

- A. Stock stroke crank 47lb minimum.

### **CONNECTING RODS:**

- A. Stock length cast or forged steel I-beam rods only.

### **PISTONS:**

- A. 4 valve relief symmetrical Flat Top pistons.
- B. Pistons may not exceed the top of the block.

### **CAMSHAFT & LIFTERS:**

- A. Hydraulic Cam and Lifters .390/.410 lift, over .410 lift add 50 lbs. Stock diameter lifters to make of engine, ex. Chev. .842"

### **CYLINDER HEADS:**

- A. Factory production open Chamber steel heads only. 70cc combustion chamber minimum. Optional head: Engine Quest 350I 70 cc minimum. No Porting or polishing allowed.
- B. Must have 1.94 intake and 1.5 exhaust valves.
- C. Steel valve retainers and keepers only.



## EAST ALABAMA MOTOR SPEEDWAY 2019 ROAD WARRIOR TECHNICAL RULES

D. Stock style rockers only long slot ok. No roller or roller tip rockers.

### **INTAKE:**

- A. Cast iron low rise intakes only. NO Bowtie intakes.
- B. 1" Carburetor adapter or spacer allowed, with .060" thick standard gaskets.

### **CARBURETOR:**

- A. 600 cfm maximum, Vacuum Secondary only. No porting or polishing, check with go-no go gauges.
- B. Quadrajet allowed.
- C. No spacers allowed.

### **FUEL SYSTEM:**

- A. Stock mount and stock replacement fuel pumps only. Carter M4891 allowed. NO Racing fuel pumps.
- B. Pump gas or racing fuel allowed.
- C. Fuel must not check above +5 on electric fuel checker when calibrated with EAMS track racing fuel.
- D. Sunoco racing fuel available at track.
- E. NO VP CHP, NO ALCOHOL, NO NITROUS OXIDE, NO E-85. GAS ONLY
- F. Safety Fuel cell mandatory, enclose in steel case, with minimum 2 steel safety straps for mounting. Must be securely mounted, and safely mounted in trunk area. If fuel line passes through driver cockpit it must be enclosed in steel conduit from rear firewall to front firewall. See safety rules for further instruction.
- G. May cut hole in trunk floor pan to mount fuel cell only.

### **IGNITION SYSTEM:**

- A. Any stock type electronic ignition with stock appearing coil and module.
- B. No MSD boxes or spark enhancing devices.

### **COOLING SYSTEM:**

- A. Heavy duty aftermarket or aluminum radiator allowed 4 or 6 blade fan mandatory.

### **EXHAUST SYSTEM:**

- A. Exhaust Manifolds only. Headers add 50 lbs, No step headers or high dollar headers.
- B. Must have exhaust pipes to divert exhaust away from driver's cockpit.



## EAST ALABAMA MOTOR SPEEDWAY 2019 ROAD WARRIOR TECHNICAL RULES

### **TRANSMISSION, REAR ENDS & CLUTCH:**

- A. Stock type manual or automatic transmission only.
- B. Stock type single disc clutch only, No triple disc or couplers, 14lb minimum flywheel. 10" Inch minimum clutch, pressure plates 16lbs. min. Solid clutch disc ok.
- C. Automatic must have stock torque converter, no dump valve.
- D. Stock rear ends or 9" Ford rear end. Floater rear end with steel parts ok.

### **BRAKES:**

- A. Disc Brakes allowed must be all stock factory type. Factory style Aluminum single piston calipers ok.

### **CHASSIS:**

- A. All Factory stock components for make of car being raced. Stock rubber motor mounts may be replaced with stock solid motor mounts. Engine must be mounted in stock location.
- B. Stock type aftermarket springs allowed, weight jacks allowed. May run tubular upper A-Arms
- C. Steel non adjustable shocks. Shocks should not be able to come apart at either end. (Meaning no snap rings, no retaining caps or anything) Crimped style only! 75.00 claim rule
- D. Both rear upper, and lower trailing arms should be same length.
- E. Stock power steering pumps and steering components.

### **BODY:**

- A. Full stock factory steel bodies only, from bumper to bumper. May use aftermarket steel or aluminum body, Plastic stock appearing bumper cover allowed on front and rear.
- B. Excessive hulling will result in weight penalty, do it right the first time. Driver's cockpit must remain open, No closing or tunneling.
- C. All glass, external glass & plastic lighting must be removed. Doors must be securely welded or bolted shut.
- D. Dash may be replaced with sheet metal, steering column may be stock or aftermarket steering shaft is optional, may use aftermarket steering wheel with quick disconnect.
- E. Full fire wall and floor pan. Must seal off trunk area from driver cockpit. Car may be boxed in. Deck must have 5 degrees or 1 ½" taper.
- F. Universal aftermarket gauges allowed.
- G. Battery must be mounted securely in trunk not in driver cockpit.
- H. 6" spoiler max 12" long side boards with 6" Height

### **ROLL CAGE:**

- A. Quality constructed safe roll cage mandatory. 6 point minimum cage properly and adequately reinforced. Roll cage must be constructed of a minimum 1 ½" tubing. .090" wall thickness. 4 driver side door bars, 2 passenger side door bars, adequately braced and welded to the frame. Front loop bar allowed may be tied in to main cage.



## EAST ALABAMA MOTOR SPEEDWAY 2019 ROAD WARRIOR TECHNICAL RULES

- B. Aluminum racing seat required must be mounted on a seat hoop with 3/8 minimum bolts. 50lb weight break for full containment seat.
- C. 3" wide, 5-point safety harness required, maximum 3 years old. Bolted securely to roll cage, not floor pan.
- D. Driver must have driver's side full size window net. No triangular or sprint car type nets.

### WHEELS & TIRES:

- A. 8" or 10" steel wheels optional Bead locks permitted. Stock lug pattern, no wide five wheels or adapters.
- B. .100" center wheel hub thickness minimum. 1/2" stud minimum with 1" lug nuts mandatory.
- C. H500 Hoosier Racing Tires only.
- D. No grooving or siping of tires.
- E. No Chemical treating or altering of tires. No tire softeners permitted. Tires will be subject to lab testing at any time to determine legality.
- F. Tires available at the track on race night or call 334-297-2594 during the week.

*NOTE: Tires must conform to benchmark when tested. No alteration of any kind is permitted.*

### PROTEST:

- G. Top End - \$250. \$50 will be retained by track.
- H. Bottom End - \$250. \$50 will be retained by track.
- I. Must protest Top End to protest Bottom End.
- J. Visual protest \$25 - \$25 will be retained by track.
- K. Clutch \$150 claim rule.
- L. Tire protest \$250 (per tire) - \$250 will be retained by track. Must finish in top 3 to protest.

### SAFETY:

- A. Steel roll over bars are mandatory and must be approved. Aluminum and other soft materials are not permitted. Front and rear roll bars must be connected at top (cage type) and bottom of both sides at seat height. Side roll bars are mandatory and must extend into door panels, (minimum of four (4) on left side and two (2) on right side with additional support on the back of the roll bar. All bars must be welded and not less than 1 1/2" O.D. steel tubing. No pipe fittings allowed.
- B. A quick release 5 point safety belt of no less than three (3) inch wide material is mandatory and must be fastened to roll bars with bolts and not less than 3/8" in diameter. Shoulder harness mandatory 3" minimum. Seat belts can be no more than 3 years old.
- C. Only approved racing helmets will be allowed. Minimum of SA2010 rating.
- D. All drivers in all divisions will be required to wear a complete fire resistant driver's suit. Fire resistant gloves, underwear and shoes are highly recommend



## **EAST ALABAMA MOTOR SPEEDWAY 2019 ROAD WARRIOR TECHNICAL RULES**

- E. All cars will be equipped with their own fully charged 2 lb. minimum fire extinguisher in good working order and installed within easy reach of the driver. On board fire extinguisher systems recommended.**
- F. Battery must be securely mounted in the trunk area of all cars. No batteries allowed in the driver's compartment.**
- G. Safety type racing fuel cell with steel outer covers are mandatory in all divisions, All fuel tanks and cells must be mounted with a minimum of 2" x 1/8" steel safety straps that completely surround tank. No gas cans or beer kegs allowed. No fuel cooling devices allowed.**
- H. All cars and drivers will be required to meet all safety regulations prior to competition. No Exceptions!**
- I. Center top of steering post must be padded with at least 2" of soft material.**
- J. Drivers must be able to exit car from either side.**
- K. All roll bars close to driver's head, arms and legs must be fully padded.**
- L. Kill switch is required within easy reach of driver.**
- M. All drive shafts must be painted white.**
- N. Window nets mandatory.**
- O. All cars must meet the safety requirements as outlined in Section D of General Track Rules for all Divisions.**
- P. E.A.M.S. reserves the right to change, omit and/or enforce any rules necessary to maintain a safe program.**