

# **CROWN VIC**

## **PROTEST:**

Positions 1-3 can protest with a \$1500 protest fee. \$1500 claim on motor. \$300 claim on CPU.

## **ENGINE/TRANSMISSION:**

- A. Engine must be completely stock.
- B. 4.6 sohc
- C. Must have mufflers.
- D. Exhaust must extend to rear tires.
- E. Catalytic convertor may be removed.
- F. Transmission must be completely stock.
- G. A.c. Condensor must be removed.

## **SAFETY:**

- A. Drivers must wear full fire suit, racing gloves, racing shoes and Helmet while on track.
- B. Hans device
- C. Racing seat and belts mandatory.
- D. Racing belt must have 5 point system.
- E. Fire extinguisher required in all cars.
- F. Battery inside driver's compartment must be inside a closed box.
- G. Battery disconnect switch on the driver side, rear speaker area.

## **TIRES/WHEELS:**

- A. Tires must be dot legal and all 4 tires must be the same size.
- B. Wheels must be stock steel and all 4 wheels must be same size and offset.
- C. No wheel spacers of any kind.



# CROWN VIC

## BODY:

- A. Front and rear bumper must remain stock with no sharp edges. Bumpers must have tow chains front and rear.
- B. No push bars in front or rear of car. No exposed bars at all.
- C. Hood and trunk may utilize stock hinges, but must be secured With hood pins.
- D. No hulling or lightening of body. The only areas on car.
- E. That may be hulled are the front driver and passenger doors.
- F. All flammable materials and glass must be removed.
- G. Any holes in front firewall and rear firewall must be covered With aluminum or steel.
- H. All cars must have numbers on front doors and roof.
- I. Steering column must remain stock, all airbags must be removed. Quick release steering wheel ok, but must be mounted to stock Steering column.
- J. Must have at least 4 vertical windshield bars in front of driver.
- K. Roll cage must be inside driver compartment only, no part of
- L. Must have stock dash in place.
- M. Four driver door bars and 3 passenger door bars minimum.
- N. Cage must be securely mounted to frame suspension.
- O. No altering of stock suspension. Cage may extend outside of Passenger compartment.
- P. No slope noses of any kind.
- Q. All doors must be closed in sheet metal, excluding drivers door only.
- R. Dash must have factory metal skeleton in original place. Flammable material can be removed.

## WEIGHT:

- A. Minimum weight 3500lbs.
- B. No adding ballast of any type to car.

## BRAKES:

- A. Must remain factory stock, all 4 corners must be operable.

## REAREND:

- A. Must be factory stock rearend with stock components.
- B. The only legal gears will be 2.73, 3.27, and 3.55.
- C. Rear differential may be locked by any means necessary, but Gear ratio rule remains the same (3.55 max gear)

## FUEL:

- A. Pump gas only, no racing fuel.
- B. Stock fuel tank and fuel pump only

